



Numerical Simulation of Non-Isothermal CO₂ Injection Using the Thermo-Hydro-Mechanical Code CODE_BRIGHT

V Vilarrasa (1,2), S Olivella (2), O Silva (3), J Carrera (1,3)

(1) GHS, Institute of Environmental Assessment and Water Research (IDAEA), CSIC, Jordi Girona 18-26, 08034 Barcelona, Spain (victor.vilarrasa@upc.edu), (2) GHS, Dept Geotechnical Engineering and Geosciences, Technical University of Catalonia (UPC-BarcelonaTech), Jordi Girona 1-3, 08034 Barcelona, Spain, (3) Fundación Ciudad de la Energía (CIUDEN), CO₂ Geological Storage Programme, II Av. de Compostilla 2, 24400 Ponferrada (León), Spain

Storage of carbon dioxide (CO₂) in deep geological formations is considered an option for reducing greenhouse gas emissions to the atmosphere. Injecting CO₂ into aquifers at depths greater than 800 m brings CO₂ to a supercritical state where its density is large enough to ensure an efficient use of pore space. However, CO₂ will always be lighter than the resident brine. Therefore, it will flow along the top of the aquifer because of buoyancy. Thus, suitable aquifers should be capped by a low-permeability rock to avoid CO₂ migration to upper aquifers and the surface.

Therefore, ensuring mechanical stability of the caprock is critical to avoid CO₂ leakage. Yet, CO₂ injection can result in significant pressure buildup, which affects the stress field and may induce large deformations (Vilarrasa et al., 2010b). These can eventually damage the caprock and open up new flow paths. Moreover, inflowing CO₂ may not be in thermal equilibrium with the aquifer, which induces stress changes that may affect the caprock stability.

We use the coupled thermo-hydro-mechanical finite element numerical code CODE_BRIGHT (Olivella et al., 1994, 1996) to simulate these processes. We have extended the code to simulate CO₂ as a non-wetting phase. To this end, we have implemented the Redlich-Kwong equation of state for CO₂. As a first step, two-phase flow studies (Vilarrasa et al., 2010a) were carried out. Next, coupled hydro-mechanical simulations were performed (Vilarrasa et al., 2010b). Finally, we have implemented CO₂ thermal properties to simulate non-isothermal CO₂ injection in deformable deep saline formations.

Coupled thermo-hydro-mechanical simulations of CO₂ injection produce a region in thermal equilibrium with the injected CO₂. The thermal transition is abrupt. A small rise in the temperature of the supercritical CO₂ region is produced by the exothermal reaction of CO₂ dissolution into the brine. An induced thermal stress change due to thermal contraction/expansion of the rock takes place in the region affected by the CO₂ injection temperature. This can compromise the stability of preexisting fractures and trigger microseismic events.

REFERENCES

Olivella S, Carrera J, Gens A, Alonso EE (1994). Non-isothermal multiphase flow of brine and gas through saline media. *Transport In Porous Media*, 15: 271–93.

Olivella S, Gens A, Carrera J, Alonso EE (1996). Numerical formulation for a simulator (CODE_BRIGHT) for the coupled analysis of saline media. *Eng. Computations*, 13: 87–112.

Vilarrasa V, Bolster D, Dentz M, Olivella S, Carrera J (2010a). Effects of CO₂ Compressibility on CO₂ Storage in Deep Saline Aquifers. *Transport In Porous Media*, 85 (2): 619–639

Vilarrasa V, Bolster D, Olivella S, Carrera J (2010b). Coupled Hydromechanical Modeling of CO₂ Sequestration in Deep Saline Aquifers. *International Journal of Greenhouse Gas Control*, 4 (6): 910–919.