



Field injection of microscale zerovalent iron for groundwater remediation

Rajandrea Sethi (1), Tiziana Tosco (1), Michela Luna (1), Francesca Gastone (1), Milica Velimirovic (2), Johan Gemoets (2), Rob Muyshond (2), Hans Sapion (3), Norbert Klaas (4), and Leen Bastiaens (2)

(1) Politecnico di Torino, Department of Environment, Land and Infrastructure Engineering - DIATI, Torino, Italy (tiziana.tosco@polito.it), (2) VITO, Mol, Belgium, (3) SAPION, Nijlen, Belgium, (4) VEGAS, University of Stuttgart, Stuttgart, Germany

In the framework of the research project SQUAREHAB (FP7 - G. A. Nr. 226565), a pilot injection test of guar gum stabilized micro-sized zerovalent iron has been designed and performed under low pressure in a CAHs contaminated site in Belgium, characterized by fine sand (hydraulic conductivity in the order of $2 \cdot 10^{-5}$ m/s) and an effective velocity equal to 0.005 m/day (1). The field application was aimed to overcome those critical aspects which hinder mZVI particles field injection, mainly due to ZVI-based colloidal suspensions instability. A shear thinning guar gum solution (2 g/l) was selected as an environmentally friendly stabilizer.

The relevant properties of the iron slurry (iron particles size and concentration, polymeric stabilizer type and concentration, slurry viscosity) were designed in the laboratory based on several tests (namely iron reactivity tests towards contaminants, sedimentation tests and rheological measurements). The slurry preparation was successfully up-scaled to the field application, allowing a fast preparation of large volumes (1 m³ at a time) of slurry with good dissolution of guar gum and effective dispersion of mZVI. Since the injection regime of iron slurries depends on subsurface geotechnical parameters, aquifer hydraulic conductivity, and fluid properties, a specific injection well and monitoring strategy have been developed in order to achieve high discharge rates and radii of influence, and a more homogeneous distribution of the iron particles through low pressure injection. The injection well has been designed and sealed in order to sustain average to high discharge rates, preventing the daylighting of the product. Moreover the well has been hydraulically tested by means of innovative water and guar gum step rate tests in order to determine the most suitable injection rate for the iron slurry. The injection of 50 kg of micro-sized iron particles (BASF, Germany), dispersed in 5 m³ of a 2 g/l guar gum suspension, was performed at a discharge rate of 1.5 m³/h. The monitoring of the process has been conducted measuring injection rate and pressure as well as iron concentration by means of a magnetic susceptometer. After the injection, the iron distribution in the subsurface was determined through liners extraction and the iron concentration measured both via non-invasive magnetic susceptibility measurements and chemical analysis.

Even if the field test was specifically designed to inject in a permeation regime, or on the threshold between permeation and fracturing, the results of monitoring injection pressure and iron distribution proved that particles migration in the porous medium occurred via preferential flow. Results will be presented as well as considerations about critical aspects related to injection via permeation.

References

1. Luna, M.; Gastone, F.; Tosco, T.; Sethi, R.; Velimirovic, M.; Bastiaens, L.; Gemoets, J.; Muyshond, R.; Sapion, H.; Klaas, N. Pilot injection of guar gum stabilized microscale zerovalent iron in a shallow aquifer via pressurized well. (in preparation).