



Urban structure damaged by differential land level lowering in the lacustrine plain of Queretaro City, Mexico

Gil H. Ochoa-González (1), Dora Carreón-Freyre (2), Pietro Teatini (3), and Mariano Cerca (2)

(1) Western Institute of Technology and Higher Education (ITESO), Jalisco, Mexico, (2) Centro de Geociencias, National Autonomous University of Mexico, Queretaro, Mexico, (3) Dept. of Civil, Environmental and Architectural Engineering, University of Padova, Padova, Italy

The Queretaro City, Central Mexico, is placed above a variety of volcanic and sedimentary materials filling a N-S trending graben, with a geomorphologic designation of volcanic valley. The stratigraphic sequence of the filling is mainly composed by lava flows interbedded with an almost 100 m thick pyroclastic unit that was easily eroded by fluvial processes during the Tertiary time. The near surface sequence in the plain is hence composed by alluvial deposits covered by organic silty and clay lacustrine materials. Moreover, as many cities in Mexico, the main source of water supply in Queretaro is groundwater. Groundwater withdrawal caused a 1-3 m/year lowering of the piezometric level and a significant consolidation of the granular materials. Currently, the depth to groundwater table in the lacustrine plain is approximately 120 m deep. The thickness of the granular material varies significantly depending on its location with respect to the normal faults delimiting the main structure of the regional graben. The consolidation on these variably-thick deposits caused differential displacements (e.g., land subsidence) of the ground surface, generating local stress accumulation and fractures. Fracture propagation to the ground surface affected most of the urban structure in the city. We present the correlation of the outcome of a geomechanical model (Ochoa-Gonzalez et al., 2013) with the measured groundwater withdrawal and faulting maps in order to investigate the contribution of the different factors determining the generation of ground fracturing, and to evaluate the associated risk of damage to urban structure in the lacustrine part of the metropolitan area.

References

G. H. Ochoa-Gonzalez, P. Teatini, D. C. Carreón-Freyre and G. Gambolati, Modeling the deformation of faulted volcano-sedimentary sequences associated to groundwater withdrawal in the Queretaro Valley, Mexico. In: MOD-SIM 2013 - Adapting to change: the multiple roles of modelling, J. Piantadosi et al. eds., The Modelling and Simulation Society of Australia and New Zealand Inc. Publ., ISBN 978-0-9872143-3-1, 2737-2743, 2013.