



Flow of a non-Newtonian fluid as a model of snow avalanches

Julia Zayko (1) and Margarita Eglit (2)

(1) Russian Federation (juliazaiko@yandex.ru), Moscow, Lomonosov Moscow state university, (2) Russian Federation (m.eglit@mail.ru), Moscow, Lomonosov Moscow state university

Non-Newtonian fluids in which the shear stresses are nonlinear functions of the shear strain rates are used to model slope flows such as snow avalanches, mudflows, debris flows. The entrainment of bottom material is included into the model basing on the assumption that in entraining flows the bed friction is equal to the shear stress of the bottom material (Issler et al, 2011). Unsteady motion down long homogeneous slopes with constant inclines is studied numerically for different flow rheologies. Variation of the velocity profile, increase of the flow depth and velocity due to entrainment as well as the value of the entrainment rate is calculated.

REFERENCES

- Issler D, M. Pastor Perez. 2011. Interplay of entrainment and rheology in snow avalanches; a numerical study. *Annals of Glaciology*, 52(58), pp.143-147
- Eglit M.E., Demidov K.S. Mathematical modeling of snow entrainment in avalanche motion. *Cold Regions Science and Technology*, 2005, Vol. 43, Issue 1-2, P. 10-23.
- Eglit M.E., Demidov K.S. Mathematical modeling of snow entrainment in avalanche motion. *Cold Regions Science and Technology*, 2005, Vol. 43, Issue 1-2, P. 10-23.