



Rapid inundation estimates using coastal amplification laws in the western Mediterranean basin

Audrey Gailler, Anne Loevenbruck, and H el ene H ebert
CEA, DAM, DIF, 91297 Aprajon, France (audrey.gailler@cea.fr)

Numerical tsunami propagation and inundation models are well developed and have now reached an impressive level of accuracy, especially in locations such as harbors where the tsunami waves are mostly amplified.

In the framework of tsunami warning under real-time operational conditions, the main obstacle for the routine use of such numerical simulations remains the slowness of the numerical computation, which is strengthened when detailed grids are required for the precise modeling of the coastline response of an individual harbor. Thus only tsunami offshore propagation modeling tools using a single sparse bathymetric computation grid are presently included within the French Tsunami Warning Center (CENALT), providing rapid estimation of tsunami warning at western Mediterranean and NE Atlantic basins scale.

We present here a preliminary work that performs quick estimates of the inundation at individual harbors from these high sea forecasting tsunami simulations.

The method involves an empirical correction based on theoretical amplification laws (either Green's or Synolakis laws). The main limitation is that its application to a given coastal area would require a large database of previous observations, in order to define the empirical parameters of the correction equation. As no such data (i.e. historical tide gage records of significant tsunamis) are available for the western Mediterranean and NE Atlantic basins, we use a set of synthetic mareograms, calculated for both fake events and well-known historical tsunamigenic earthquakes in the area. This synthetic dataset is obtained through accurate numerical tsunami propagation and inundation modeling by using several nested bathymetric grids of increasingly fine resolution close to the shores (down to a grid cell size of 3m in some Mediterranean harbors).

Non linear shallow water tsunami modeling performed on a single 2' coarse bathymetric grid are compared to the values given by time-consuming nested grids simulations (and observation when available), in order to check to which extent the simple approach based on the amplification laws can explain the data. The idea is to fit tsunami data with numerical modeling carried out without any refined coastal bathymetry/topography. To this end several parameters are discussed, namely the bathymetric depth to which model results must be extrapolated (using the Green's law), or the mean bathymetric slope to consider near the studied coast (when using the Synolakis law).