



Towards real-time assimilation of crowdsourced observations in hydrological modeling

Maurizio Mazzoleni (1), Martin Verlaan (2), Leonardo Alfonso (1), Daniele Norbiato (3), Martina Monego (3), Michele Ferri (3), Dimitri Solomatine (1,2)

(1) UNESCO-IHE Institute for Water Education, Delft, The Netherlands, (2) Deltares, Delft, The Netherlands, (3) Alto Adriatico Water Authority, Venice, Italy, (4) Delft University of Technology, Water Resources Section, Delft, The Netherlands

The continued technological advances have stimulated the spread of low-cost sensors that can be used by citizens to provide crowdsourced observations (CO) of different hydrological variables. An example of such low-cost sensors is a staff gauge connected to a QR code on which people can read the water level indication and send the measurement via a mobile phone application. The goal of this study is to assess the combined effect of the assimilation of CO coming from a distributed network of low-cost sensors, and the existing streamflow observations from physical sensors, on the performance of a semi-distributed hydrological model.

The methodology is applied to the Bacchiglione catchment, North East of Italy, where an early warning system is used by the Alto Adriatico Water Authority to issue forecasted water level along the river network which cross important cities such as Vicenza and Padua.

In this study, forecasted precipitation values are used as input in the hydrological model to estimate the simulated streamflow hydrograph used as boundary condition for the hydraulic model. Observed precipitation values are used to generate realistic synthetic streamflow values with various characteristics of arrival frequency and accuracy, to simulate CO coming at irregular time steps. These observations are assimilated into the semi-distributed model using a Kalman filter based method.

The results of this study show that CO, asynchronous in time and with variable accuracy, can still improve flood prediction when integrated in hydrological models. When both physical and low-cost sensors are located at the same places, the assimilation of CO gives the same model improvement than the assimilation of physical observations only for high number of non-intermittent sensors. However, the integration of observations from low-cost sensors and single physical sensors can improve the flood prediction even when small a number of intermittent CO are available. This study is part of the FP7 European Project WeSenseIt Citizen Water Observatory ([www.http://wesenseit.eu](http://wesenseit.eu)).