Geophysical Research Abstracts
Vol. 18, EGU2016-14729, 2016
EGU General Assembly 2016


# COSMO-SkyMed sensor constellation and GPS data to study the source responsible of ground deformation beneath the urban area of Naples (Southern Italy) in 2012-2013.

Susi Pepe
IREA-CNR, Naples, Italy (pepe.s@irea.cnr.it)

To understand uplift phenomenon occurred during the April 2012 - January 2013 time interval at Campi Flegrei caldera, we exploited the displacement time series obtained by processing 90 SAR images acquired from the COSMO-SkyMed sensor constellation along ascending orbits via the well-known DInSAR algorithm referred to as SBAS algorithm, and the measurements provided by 14 continuous GPS stations deployed within the caldera and belonging to the permanent INGV-OV monitoring network. In particular, the caldera has shown a rapid uplift of about 6 cm with a peak rate of about 3 cm/month in December 2012. This event led the Italian Civil Protection to raise the alert level of the volcano from green to yellow.
Using a novel geodetic inversion technique we imaged the kinematics of the intrusion of a magmatic sill beneath the town of Pozzuoli at a depth of about 3100 m. The retrieved kinematics was then used as input to infer the dynamics of the sill intrusion using a recently developed numerical model.
The best fit obtained by non-linear inverse approach that consider a time-varying deformation field is a penny-shaped source located at a depth of 3100 m.
To study the detail of the intrusion process we have applied a geodetic imaging technique to determine the spatial and temporal kinematics of the ground deformation source in the selected period. The retrieved temporal pattern of the source geometry reflects that of a growing sill that, at the end of the considered period, has a roughly elliptical geometry with an extension of about 6 km in the EW direction and about 4 km in the NS one. The maximum aperture of the sill is of about 30 cm at its center.
To understand the dynamics of this phenomenon we used a numerical model of the emplacement of a magmatic sill, to fit the retrieved geometry. The parameters to be determined are: the average magma viscosity, the amount of magma already present in the sill before the 2012-2013 episode and the magma injection rate. Results show that the most likely value for the viscosity is between 103-104 Pa•s and that to justify the observed deformation pattern it is required that the reservoir should have contained at least 1010 kg of liquid magma before 2012. The injection rate has two main peaks on September and December 2012, and a smaller one on March 2013. The first two peaks have a value of about 400 kg/s and duration of 3-4 months. The total amount of injected magma is of about 8.2•1010 kg. The magma viscosity value is compatible with that of the most common magmas erupted in the past 40 ky: phonolites.
The first injection peak is associated with a seismic swarm, located beneath the town of Pozzuoli. The swarm consisted in about 200 earthquakes (maximum magnitude 1.8) occurring within an interval of about 1.5 hours. The hypocenters were located outside the area usually affected by microearthquakes in the previous years.
Our finite element structural mechanical modeling shows that the inferred source caused a marked increase in the maximum shear stress along the rim of the sill. In fact, hypocenters were located very close to the northern edge of the growing magmatic reservoir. Our findings suggest a key to interpret the caldera unrest that, started about 60 years ago, has led to a maximum uplift in the area of more than 3 m. Consequently, the observed uplift phenomenon could be interpreted in terms of injection of limited magma batches feeding the growth of a shallow magmatic reservoir. Similar mechanisms have been inferred for other calderas, where the repeated emplacement of magmatic sills has been recognized having an important role in the evolution of the volcano. Accordingly, the observation of short evolution of volcanic precursory phenomena as well as the development of innovative real-time analysis techniques should be taken into account for an effective surveillance of the Campi Flegrei caldera.
This work has been supported by MED-SUV project (European Union's Seventh Programme for research, technological development and demonstration under grant agreement No 308665) and by the Italian Department of Civil Protection and by the Italian Space Agency under theSAR4Volcanoes project (agreement n. I/034/11/0).