

## **Post-injection feasibility study with the reflectivity method for the Ketzin pilot site, Germany (CO<sub>2</sub> storage in a saline aquifer)**

Alexandra Ivanova (1), Thomas Kempka (1), Fei Huang (2), Magdalena Diersch [Gil] (1), and Stefan Lüth (1)  
(1) GFZ Potsdam, Germany, (2) Uppsala University, Sweden

3D time-lapse seismic surveys (4D seismic) have proven to be a suitable technique for monitoring of injected CO<sub>2</sub>, because when CO<sub>2</sub> replaces brine as a free gas it considerably affects elastic properties of porous media. Forward modeling of a 4D seismic response to the CO<sub>2</sub>-fluid substitution in a storage reservoir is an inevitable step in such studies. At the Ketzin pilot site (CO<sub>2</sub> storage) 67 kilotons of CO<sub>2</sub> were injected into a saline aquifer between 2008 and 2013. In order to track migration of CO<sub>2</sub> at Ketzin, 3D time-lapse seismic data were acquired by means of a baseline pre-injection survey in 2005 and 3 monitor surveys: in 2009, 2012 and in 2015 (the 1st post-injection survey). Results of the 4D seismic forward modeling with the reflectivity method suggest that effects of the injected CO<sub>2</sub> on the 4D seismic data at Ketzin are significant regarding both seismic amplitudes and time delays. These results prove the corresponding observations in the real 4D seismic data at the Ketzin pilot site. But reservoir heterogeneity and seismic resolution, as well as random and coherent seismic noise are negative factors to be considered in this interpretation. Results of the 4D seismic forward modeling with the reflectivity method support the conclusion that even small amounts of injected CO<sub>2</sub> can be monitored in such post-injected saline aquifer as the CO<sub>2</sub> storage reservoir at the Ketzin pilot site both qualitatively and quantitatively with considerable uncertainties (Lüth et al., 2015).

### Reference:

Lueth, S., Ivanova, A., Kempka, T. (2015): Conformity assessment of monitoring and simulation of CO<sub>2</sub> storage: A case study from the Ketzin pilot site. - *International Journal of Greenhouse Gas Control*, 42, p. 329-339.