Comparison of time-lapse pressure tomography and seismic tomography for characterizing a CO₂ plume in a deep saline formation

Linwei Hu¹, Joseph Doetsch¹, Ralf Brauchler², Peter Bayer¹

¹ Department of Earth Sciences, ETH Zurich, Sonneggstrasse 5, CH-8092, Zurich (linwei.hu@erdw.ethz.ch) ² AF-Consult Switzerland Ltd, Täfernstrasse 26, CH-5405, Baden

Introduction

Geophysical surveys, such as seismic tomography (ST), are preferably used for characterizing reservoirs and CO₂ plumes, However, proper petrophysical model is required, which is usually nonlinear and indirectly related to the hydraulic conditions. Pressure tomography (PT) is a novel approach for tracking an evolving CO₂ plume by directly relating the CO₂ saturation to the variations in flow properties. By this approach, pressure transients are utilized for inverting the plume shape and estimating CO₂ saturation.

Objective

- Examine the inversion performance of cross-well PT and ST
- Compare and combine the inversion results by clustering them in an individual or joint way
- Calculate the CO₂ saturation by the mixed-phase specific storage in a single-phase proxy

Diffusivity and velocity tomograms

- Aquifer structure prior to CO₂ injection can be recognized from inverted diffusivity.
- Inverted velocity cannot reconstruct the hydrofacies.
- Inversion results from both PT and ST cannot reproduce the "true" diffusivities and velocities, as well as their differences.
- Direct transformation of the inverted values causes an underestimation of the CO₂ saturation



Figure 1. "true" vs. inverted results in three scenarios. The left and right two columns show the tomograms derived from PT and ST, respectively. For each scenario, the first row displays the diffusivity and velocity tomograms prior to CO₂ injection. The second and third rows give the results of diffusivity and velocity differences, respectively.

- PT resolves the more vertical-like shape due to the larger variance of hydraulic travel times
- Heterogeneity masks the plume in the highly permeable layer for PT
- Combination of the results provides a better estimation of the main plume shape

Forward simulation

Model set-up

responder

 $k = 1 \times 10^{-13} \, (m/s)$

 $_{1}=1\times10^{-12}$ (m/s)

 $k_2 = 1 \times 10^{-13} \, (m/s)$

 $k_2 = 1 \times 10^{-12} \, (m/s)$

injector

caprock

reservoir

bottom seal

50 m

homo

2layers_A

2layers_B

• Test sequence

step 1: baseline study

- Implement PT by multilevel brine injection tests
- Implement ST by P-wave pulses

step 2: CO₂ injection

Generate CO₂ plumes by different injection rates and durations (short, long)

step 3: shut-in

- Let the pressures recover (nearly)
- back to the initial condition • Prepare the next experiments
- step 4: repetition of PT and ST
- Implement PT by multilevel CO₂ injection tests
- Implement ST by P-wave pulses

Travel-time inversion

hydraulic travel time



Results and discussion

Individual and joint clustering structures

• Individual clustering results are comparable in the scenarios "homo" and "2layers_A"



Figure 2. Individual and joint clustering results according to the inverted tomograms. The numbers in each tomogram present the information of pixel misclassification error rate (blue: overestimate rate; green: underestimate rate; red: total misclassification rate).

Calculated CO₂ saturations

- the individual clustering structures
- saturation of each secondary plume





EGU2016-12097

seismic travel time

$$t = \int_{x_1}^{x_2} \frac{ds}{V}$$

Difference inversion [3]

 $\Delta t = t_{post} - t_{pre}$



Clustering

- Base on a modified k-means approach
- Centroids of the clusters are determined by data histogram
- Data distribution is composed of two or more Gaussian functions
- Reservoir structure is reconstructed by clustering inverted diffusivities
- Plume extent is determined by clustering the diffusivity or velocity difference individually (1-D clustering) or jointly (2-D clustering)



2-D clustering



• The errors between the "true" and calculated saturations (1-plume) show a strong correlation with the underestimation rate

• The errors of the joint clustering structures remain in a smaller range compared to

• Two secondary plumes are distinguished based on the identified aquifer structure • Calibration of the mixed-phase specific storage (2-plume) provides insight in the

structures compared to "true" saturations. The plume is depicted with an integrated value of saturation. The white dot line indicates the boundary of two adjacent layers.



Figure 4. Saturations of individual and joint clustering structures comared to "true" saturations. The plume consists of two "secondary plumes", and each plume has an integrated saturation value. The white dot line indicates the boundary of two adjacent layers.







ETH

Eidgenössische Technische Hochschule Zürich Swiss Federal Institute of Technology Zurich





Conclusions

- The structure of the reservoir prior to CO₂ injection can be reconstructed by PT, which can be utilized as a prior information for the following zonal calibration.
- In general, the capability of reproducing the plume shape is comparable for PT and ST. However, neither PT nor ST can directly quantify the saturation by the inverted values.
- PT can resolve more vertical-like shape due to the larger variance of hydraulic travel times. Heterogeneity of the permeability can however readily mask the plume in highly conductive layer.
- Joint clustering can alleviate the underestimation of the plume shape, which is essential for reducing the errors of estimated saturations.
- PT can complement ST by improving the delineation of plume shape and estimated saturations.

References

We are grateful for the funding from the EU 7th Framework Programme FP7 under grant number 309067, project TRUST.

[1] Hu, L., Bayer, P., Alt-Epping, P., Tatomir, A., Sauter, M., and Brauchler, R. (2015). Time-lapse pressure tomography for characterizing CO₂ plume evolution in a deep saline aquifer. Int. J. Greenh. Gas Control, 39, 91–106.

[2] Hu, L., Bayer, P., and Brauchler, R. (2016). Detection of carbon dioxide leakage during injection in deep saline formations by pressure tomography. Water Resour. Res., under revision.

[3] Doetsch, J., Linde, N., and Binley, A. (2010). Structural joint inversion of time-lapse crosshole ERT and GPR traveltime data. Geophys. Res. Lett., 37, L24404.