



Elastic and creep strain heterogeneity observed in Green River shale samples by synchrotron X-ray micro-tomography and image registration.

Hiroki Sone (1), Cecilia Cheung (1), Mark Rivers (2), Yanbin Wang (2), and Tony Yu (2)

(1) Department of Civil and Environmental Engineering, University of Wisconsin-Madison, Madison, USA, (2) Center for Advanced Radiation Sources, University of Chicago, Chicago, USA

Accurate knowledge about the time-dependent constitutive behavior of geological materials is essential when forecasting the production potential of shale reservoirs or evaluating the long-term seal integrity of a subsurface waste repository. To this end, it is not only important to measure the bulk time-dependent behavior of the rock, but also important to understand the microscale mechanism responsible for the bulk behavior in order to predict the long-term behavior from limited information about the rock. We conducted creep experiments using Green River shale samples while obtaining synchrotron X-ray images in order to capture the microscale strain-partitioning that occurs within the sample. Cylindrical shale samples of 2-3 millimeter diameter and height were stressed up to 40 MPa by small deformational apparatus with an X-ray transparent load frame, after which the load was held constant to allow creep deformation for up to 4 months. Tomographic images of about 3-micron resolution were reconstructed from images collected at different timings of the experiment, which allowed us to analyze where the rock is deforming with the aid of volumetric image registration. Displacement fields and strain fields recovered from the analysis showed that both elastic and creep strain was larger at portions of the rock where the organic content is higher. Elastic constants calculated from the stress and strain magnitudes agree with measurements with larger samples by conventional methods. The creep compliance estimated from the results is also in general agreement with values measured from larger samples.