



Measuring Methane from Cars, Ships, Airplanes, Helicopters and Drones Using High-Speed Open-Path Technology

George Burba (1), Tyler Anderson (2), Sebastien Biraud (3), Dana Caulton (4), Joe von Fischer (5), Beniamino Gioli (6), Chad Hanson (3,7,8), Jay Ham (5), Katrin Kohnert (9), Eric Larmanou (9), Peter Levy (10), Andrea Polidori (11), Olga Pikelnaya (11), Torsten Sachs (9), Andrei Serafimovich (9), Alessandro Zaldei (6), Mark Zondlo (4), and Rommel Zulueta (12)

(1) LI-COR Biosciences, Lincoln, USA (george.burba@licor.com), (2) Apple Computer, Cupertino, USA, (3) AmeriFlux-LBNL, Berkeley, USA, (4) Princeton University, Princeton, USA, (5) Colorado State University, Fort Collins, USA, (6) CNR-The Institute of Biometeorology, Florence, Italy, (7) Oregon State University, Corvallis, USA, (8) Atlatl Sensing, Corvallis, USA, (9) GFZ German Research Centre for Geosciences, Potsdam, Germany, (10) Centre for Ecology & Hydrology, Edinburgh, United Kingdom, (11) South Coast Air Quality Management District, Diamond Bar, USA, (12) National Ecological Observatory Network, Boulder, USA

Methane plays a critical role in the radiation balance, chemistry of the atmosphere, and air quality. The major anthropogenic sources of methane include oil and gas development sites, natural gas distribution networks, landfill emissions, and agricultural production.

The majority of oil and gas and urban methane emission occurs via variable-rate point sources or diffused spots in topographically challenging terrains (e.g., street tunnels, elevated locations at water treatment plants, vents, etc.). Locating and measuring such methane emissions is challenging when using traditional micrometeorological techniques, and requires development of novel approaches. Landfill methane emissions traditionally assessed at monthly or longer time intervals are subject to large uncertainties because of the snapshot nature of the measurements and the barometric pumping phenomenon. The majority of agricultural and natural methane production occurs in areas with little infrastructure or easily available grid power (e.g., rice fields, arctic and boreal wetlands, tropical mangroves, etc.).

A lightweight, high-speed, high-resolution, open-path technology was recently developed for eddy covariance measurements of methane flux, with power consumption 30-150 times below other available technologies. It was designed to run on solar panels or a small generator and be placed in the middle of the methane-producing ecosystem without a need for grid power.

Lately, this instrumentation has been utilized increasingly more frequently outside of the traditional use on stationary flux towers. These novel approaches include measurements from various moving platforms, such as cars, aircraft, and ships. Projects included mapping of concentrations and vertical profiles, leak detection and quantification, mobile emission detection from natural gas-powered cars, soil methane flux surveys, etc.

This presentation will describe the latest state of the key projects utilizing the novel lightweight low-power high-resolution open-path technology, and will highlight several novel approaches where such instrumentation was used in mobile deployments in urban, agricultural and natural environments by academic institutions, regulatory agencies and industry.