



How much suspended particulate matter enters long-term in-channel storage?

Stephan Dietrich, Carmen Kleisinger, Nora Kehl, Birgit Schubert, and Gudrun Hillebrand
Federal Institute of Hydrology (BfG), Koblenz, Germany (dietrich@bafg.de)

The route of suspended particulate matter (SPM) downstream rivers strongly depends on discharge conditions and involves transport times and periods with resting times in deposits e.g. at areas with low-flow conditions near the channel bed. It is, however, difficult to estimate the contribution of SPM on the bed load.

In this study, particle-bound polychlorinated biphenyls (PCB), which were released by an incident in the Elbe river (Central Europe) in spring 2015, could be used as unique tracer for transport pathways of SPM along the whole river stretch (over 700 km length), including low mountain ranges, lowlands, and the estuary. In 2015 the Elbe River was characterized by low-discharge conditions. Thus, the export of SPM on flood plains was strongly limited.

The incident was monitored by concentration measurements of seven indicator PCB congeners along the inland part of the Elbe River as well as in the Elbe estuary. Data from ten monitoring stations (settling tanks) are considered. The total PCB load is calculated for all stations on the basis of monthly contaminant concentrations and daily suspended sediment concentrations. Monte-Carlo simulations assess the uncertainties of the calculated load. It is shown that the ratio of high versus low chlorinated PCB congeners is a suitable tracer to distinguish the PCB load of the incident from the long-term background signal (hereafter PCB6 ratio). We demonstrate that both the load of PCB as well as its chemical fingerprint allows the estimation of transport durations for the transport processes involved.

Only a little part of the suspension has been transported via wash load. The PCB6 ratio is used to estimate mean transport velocities of the wash load fraction. A direct transport of wash load via the mean flow velocity of the water was not observed. Shortly after the incident, the PCB6 ratio was monitored 257 km downstream of the incident site in April 2015, in May first occurrence was monitored 514 km downstream of the incident site and in July it reaches the tidal weir 626 km downstream and enters the estuary. Here the transport velocity strongly decreases and the PCB6 ratio was not detected 25 km downstream the tidal weir before December 2015.

The major part of the PCB-marked suspension is transported via suspended load. Interestingly, the reduction of total PCB tagged SPM load within the first 514 km downstream of the incident site indicates that roughly 75% of the annual SPM load (of the most upstream monitoring station located 43 km downstream of the incident site) is stored in the sediments of the Elbe River, suggesting that suspended sediment in transport enters storage after a relatively short distance. Once SPM settles, significant storage can occur over decadal time scales.