



Gas hydrate exploitation from subsea reservoirs in the Black Sea

Georg Janicki, Stefan Schlüter, Torsten Hennig, and GÖrge Deerberg

Fraunhofer Institute for Environmental, Safety, and Energy Technology UMSICHT, Processes, Oberhausen, Germany
(georg.janicki@umsicht.fraunhofer.de)

Natural gas is the most environmental friendly source of fossil energy. When coal is replaced by natural gas in power production the emission of carbon dioxide is reduced by ~50 %. The vast amount of natural gas assumed in subsea gas hydrate deposits can help to overcome a shortage of fossil energy resources in the future. To increase their potential for energy applications new technological approaches are being discussed and developed worldwide. Besides technical challenges that have to be overcome climate and safety issues have to be considered before a commercial exploitation of such unconventional reservoirs.

The potential of producing natural gas from subsea gas hydrate deposits by various means (e. g. depressurization and/or carbon dioxide injection) is numerically studied in the frame of the German research project »SUGAR - Submarine Gas Hydrate Reservoirs«. In order to simulate the exploitation of hydrate-bearing sediments in the subsea, an in-house simulation model HyReS which is implemented in the general-purpose software COMSOL Multiphysics is used. This tool turned out to be especially suited for the flexible implementation of non-standard correlations concerning heat transfer, fluid flow, hydrate kinetics, and other relevant model data. Partially based on the simulation results, the development of a technical concept and its evaluation are the subject of ongoing investigations, whereby geological and ecological criteria are to be considered.

A promising area for gas hydrates within European waters is the Black Sea. Therefore, the work is focused on the natural gas exploitation from a deposit located in the Danube delta within a deep sea fan around 200 km off shore Bulgaria. The simulations illustrate the processes and effects occurring during the gas production from a subsea gas hydrate deposit by simple depressurization. The behavior of relevant process parameters such as pressure, temperature and phase saturations as well as the gas production performance have been evaluated. The results reveal that the production of natural gas is possible but with quite low rates. Based on a case study for the Black Sea deposit it can be shown that the hydrate decomposition and thus the natural gas production strongly depend on the geophysical properties of the reservoir, the mass and heat transport within the reservoir, and the model settings. In particular, the permeability and the available heat, which is required for the decomposition of the hydrate, play an important role.