



## **Magnetotelluric data acquisition and processing on the volcanic island of La Palma (Canary Islands, Spain)**

David Martínez van Dorth (1), Ziqi Emily Niu (2), Kay R. Royo (3), Rajbir S. Sandhu (4), Kate M. Nelson (5), Federico Di Paolo (1), Katarzyna Slezak (1), Iván Cabrera Pérez (1), Alba Martín Lorenzo (6), Juanjo Ledo (1,7), Nemesio M. Pérez (1,6,8)

(1) Instituto Volcanológico de Canarias (INVOLCAN), San Cristóbal de La Laguna, Spain (dmartinez@iter.es), (2) Department of Earth Science, University College London, London (emily.niu.17@ucl.ac.uk), (3) Department of Earth and Environmental Sciences, California State University, East Bay, Hayward, CA, U.S.A. (kroyo@horizon.csueastbay.edu), (4) Department of Earth Science and Engineering, Imperial College London, Kensington, U.K. (rajbir\_97@yahoo.co.uk), (5) Department of Earth and Atmospheric Sciences, University of Northern Colorado, Greeley, CO, U.S.A. (nels0274@bears.unco.edu), (6) Instituto Tecnológico y de Energías Renovables (ITER), Granadilla de Abona, Spain (alba.martin.beca@iter.es), (7) GEOMODELS Research Institute, Departament de Dinàmica de la Terra i de l'Oceà, Facultat de Ciències de la Terra. Universitat de Barcelona. Barcelona, Spain (jledo@ub.edu), (8) Agencia Insular de la Energía de Tenerife (AIET), Granadilla de Abona, Spain (nperez@iter.es)

The magnetotelluric method (MT) is a geophysical technique successfully applied to map the presence of fluids or image significant structural contrasts in the subsurface. Obtaining magnetotelluric data in a volcanic island environment might be a challenging task due to the complicated topography and the rough terrain. The goal of this study is to infer the major conductive structures related to the geothermal system of La Palma island (Spain).

In the presented work, a dataset of 44 new magnetotelluric soundings distributed around the island has been acquired from June to August 2018. The instrumentation consisted of four Metronix ADU-08e, equipped with EPF-06 electrodes and MFS-06e magnetic coils. Only horizontal electric ( $E_x$ ,  $E_y$ ) and magnetic ( $H_x$ ,  $H_y$ ) fields have been recorded, acquired along NS and EW magnetic directions. Two remote stations were installed.

Data processing was carried out by employing the robust remote-reference scheme of Egbert and Booker (1986). We obtained the magnetotelluric response functions for periods in the range of 0.001s - 1000s, depending on the stations quality. Dimensionality and strike analysis has been performed based on the phase tensor (Caldwell et al., 2004) and the WALDIM (Martí et al., 2009) decomposition, showing a 3D behavior of the resistivity distribution over the island.

Caldwell, T. G., Bibby, H. M., & Brown, C. (2004). The magnetotelluric phase tensor. *Geophysical Journal International*, 158(2), 457-469.

Egbert, G. D., & Booker, J. R. (1986). Robust estimation of geomagnetic transfer functions. *Geophysical Journal of the Royal Astronomical Society*, 87(1), 173-194.

Martí, A., Queralt, P., & Ledo, J. (2009). WALDIM: A code for the dimensionality analysis of magnetotelluric data using the rotational invariants of the magnetotelluric tensor. *Computers & Geosciences*, 35(12), 2295-2303.