

EGU2020-7117

<https://doi.org/10.5194/egusphere-egu2020-7117>

EGU General Assembly 2020

© Author(s) 2021. This work is distributed under the Creative Commons Attribution 4.0 License.



Geostructural complexity and passive seismic surveys: a geostatistical analysis in the Kathmandu basin

Sebastiano Trevisani¹, Dev Kumar Maharian², Denis Sandron³, Surya Narayan Shrestha², Sarmila Paudyal², Franco Pettenati³, and Massimo Giorgi³

¹University IUAV of Venice (Venice, Italy)

²National Society for Earthquake Technology (Kathmandu, Nepal)

³OGS, National Institute of Oceanography and Applied Geophysics, (Trieste - Italy)

In this study a set of 39 single station passive seismic surveys conducted in the Kathmandu basin (Nepal), based on the horizontal to vertical spectral ratio methodology (HVSr), is analyzed by means of a geostatistical approach. The Kathmandu basin is characterized by a heterogeneous sedimentary cover and by a complex geostructural setting, inducing high spatial variability of the bedrock depth. In relation to the complex geological setting, the interpretation and analysis of HVSr data are challenging, both from the perspective of bedrock depth analysis as well as of seismic site effects detection. In order to maximize the broad range of information available, the HVSr data are analyzed according to a geostatistical approach. First, the spatial continuity structure of HVSr data is analyzed and interpreted taking into consideration the geological setting and available stratigraphic and seismic information. In addition, we test the possibility to integrate the analysis with potential auxiliary variables, derived from geomorphometric variables and considering the distance from outcropping bedrock. The explorative geostatistical analysis confirms the complexity of the geo-structural setting of the area. Finally, a mapping of HVSr resonance periods, with the evaluation of interpolation uncertainty, is obtained by means of ordinary kriging interpolation. The resulting map, even if characterized by a large interpolation support, is congruent with the geo-structural setting and the main lineaments of the area. The adopted approach is particularly useful in the context of micro-zonation studies based on HVSr methodology conducted in historical urban areas. Moreover, this work contributes to the geo-structural knowledge of the deep structure of the Kathmandu basin.

References

Paudyal YR, Yatabe R, Bhandary NP, Dahal RK, 2013. Basement topography of the Kathmandu Basin using microtremor observation. *J Asian Earth Sci* 62:627–637, doi.org/10.1016/j.jseaes.2012.11.011.

Nakamura Y., 1989. A method for dynamic characteristic estimation of subsurface using microtremors on the ground surface. *Quart. Rep. Railway Tech. Res. Inst.* 30, 25-33

Sandron D., S. Maskey, M. Giorgi, D. V. Maharjan, S. N. Narayan, C. Cravos, F. Pettenati, 2019.

Environmental and on buildings noise measures: Lalipur (Kathmandu). *Earthquake Engineering*. Vol. 60, n. 1, 17-38: March 2019, doi 10.4430/bgta0259.

Trevisani S., Boaga J., Agostini L., Galgaro A., 2017. Insights into bedrock surface morphology using low-cost passive seismic surveys and integrated geostatistical analysis. *Science of the Total Environment*, 578, 186-202, <http://dx.doi.org/10.1016/j.scitotenv.2016.11.041>.