
# Modelling the effects of permeability, groundwater flow and water table depth on landscape evolution

Elco Luijendijk, University of Göttingen, <u>elco.luijendijk@geo.uni-goettingen.de</u> EGU2020: Sharing Geoscience Online, 5 may 2020

- Motivation: Explore the relation between groundwater flow, drainage density and erosion
- How: Model experiments with a new model code that combines groundwater flow, saturation excess overland flow, hillslope and stream erosion
- Conclusion: Groundwater flow & transmissivity exert a strong control on drainage density and erosion. Lower
  watertable gradients result in a higher chance that fast eroding streams draw the watertable below adjacent
  streams, which results in streams falling dry.
- Click on the following links for more details: model description, model experiment <u>1</u>, <u>2</u>, <u>3</u>, <u>comparison modeled</u> land surface, and <u>evolution over 100,000 years</u>








### **Description groundwater flow &** erosion model code

- Philosophy: Construct the simplest possible groundwater flow & erosion model
- Cross-sectional 1.5 D model of groundwater, overland flow and erosion for 100,000 years, starting with a random initial topography
- Analytical solution to steady-state groundwater flow
- Saturation excess overland flow: Flow generated where precipitation exceeds available storage above the steady-state watertable & instantaneous drainage
- Erosion follows standard eqs. of most landscape evolution models. Precipitation statistics based on data from the Netherlands (~average humid climate)
- Different timescales overland flow & baseflow: new analytical solution to integrated erosion by overland flow per precipitation event




Initial calculated watertable and baseflow at the start of a model run with a randomly generated topography



#### **Model experiment 1: Moderate** transmissivity

- Moderate transmissivity (hydraulic conductivity x aquifer thickness) =  $10^{-3} \text{ m}^2/\text{sec} = \text{-medium grained}$ sand
- Moderate stream density after 100,000 yrs: 1 stream per 700 m
- Note the presence of abandoned stream channels where faster eroding streams have drawn the watertable below slower streams, causing them to fall dry




Modelled position of the land surface and watertable over 100 kyr. Note that the topography looks somewhat odd due to the very high aspect ratio of the figure

#### Model experiment 2: Low transmissivity

- Low  $T = 10^{-4} \text{ m}^2/\text{sec} = \text{silt}$
- Very high stream density, 1 stream per 150 m
- Very little abandonment of streams. High curvature of watertable means that watertable difficult to detach from neighbouring streams





Modelled position of the land surface and watertable over 100 kyr. - no stream left behind -










#### Model experiment 3: High transmissivity

- High T=  $10^{-2}$  m<sup>2</sup>/sec =~coarse sand
- Much lower drainage density, only one stream survives = 1 stream per 10000 m
- Much higher rate of incision: More groundwater flow drained per stream, and therefore higher erosion rates






intro | methods | results | back | forward

## **Comparison three model experiments**

of the subsurface exerts a strong control on drainage density and incision rates:




Comparison modelled position of the land surface and watertable over 100 kyr from low transmissivity (left) to high transmissivity (right)

Comparison of three model experiments show that the hydraulic conductivity / transmissivity

## **Comparison modelled evolution over 100 kyr**

- being abandoned after 100,000 years



Comparison modelled stream density, water fluxes and erosion over 100 kyr from low transmissivity (left) to high transmissivity (right)

intro methods results back forward

• Reaction time of high transmissivity model run is much faster than the moderate transmissivity model run where streams are still

• After initial phase these systems are dominated by groundwater discharge (baseflow). Results may be different for systems controlled by overland flow, i.e. higher precipitation or lower storage potential (drainable porosity) in unsaturated zone

