Active seismic monitoring of CO₂-saturated brine injection into a fault (CS-D experiment in the Mont Terri Rock Laboratory)



SCCER

Melchior Grab¹, Alba Zappone^{1,2}, Antonio P. Rinaldi³, Sebastian Hellmann¹, Quinn Wenning¹, Clément Roques¹, Anne Obermann³, Claudio Madonna¹, Yves Guglielmi⁴, Christophe Nussbaum⁵, Hansruedi Maurer¹, and Stefan Wiemer³

1 Department of Earth Science, ETH Zurich, Zürich, Switzerland; 2 Department of Mechanical and Process Engineering, ETH Zurich, Zürich, Switzerland; 3 Swiss Seismological Service, ETH Zurich, Zürich, Switzerland; 4 Energy Geosciences Division, LBNL, Berkeley CA, USA; 5 Federal Office of Topography, Swisstopo, St-Ursanne, Switzerland



This work is licensed under the Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License.



Introduction: CS-D experiment in the Mont Terri Laboratory



After Nussbaum et al. (2017): Tectonic evolution around the Mont Terri rock laboratory, northwestern Swiss Jura: constraints from kinematic forward modelling. Swiss Journal of Geosc., 110, DOI 10.1007/s00015-016-0248-x.



Grab et al. (https://doi.org/10.5194/egusphere-egu2020-21588)

Flow through faults, potential leaks through a cap rock:



Simulating CO₂ (dissolved in formation water) leaking trough a fault in a caprock

Objectives of the CS-D experiment:

- investigating how the exposure to CO₂-rich brine affects sealing integrity of a caprock, hosting a fault system (permeability changes, induced seismicity).
- observing directly the fluid migration along a fault and its interaction with the surrounding environment.
- testing instrumentation and methods for monitoring and imaging fluid transport.

More about the CS-D experiment:

Wenning et al., "Fault hydromechanical characterization and CO₂-saturated water injection at the CS-D experiment, Mont Terri Rock Laboratory" (EGU2020-19243)

Zappone et al. "CO2 Sequestration: Studying Caprock And Fault Sealing Integrity, The CS-D Experiment In Mont Terri." *Fifth CO2 Geological Storage Workshop*. Vol. 2018. No. 1. European Association of Geoscientists & Engineers, 2018.



3

Introduction: Layout of the CS-D experiment

CO₂-Injection:

Injection of CO₂-saturated formation water into the main fault in Mont Terri

Borehole D1:

4 intervals for fluid injection within the core of main fault and in its close vicinity.

Borehole D2

6 intervals for fluid sampling and hydraulic/geochemical monitoring.



Geophysical monitoring:

Various equipment in boreholes and in the gallery for active and passive seismic monitoring and DC-resistivity monitoring. Here, the active seismic monitoring is presented.



Grab et al. (https://doi.org/10.5194/egusphere-egu2020-21588)



Methods: Data acquisition

The active seismic monitoring experiment presented here was conducted with seismic sources in borehole D4 and a geophone array cemented in D5.

Sources:

- P-Wave sparker source
- For tomographic imaging: source fired every 25 cm
- For time-lapse monitoring during step-up injection: source fired from constant location for better repeatability.

Geophone array:

- 24 three-component geophones
- 50 cm spacing
- Cemented, for optimum coupling and repeatability over long times







Methods:

Data processing and seismic tomographic imaging

Processing Workflow:

- 1. Bandpass / Dewow filtering
- T₀ correction by cross-correlating trigger-signals
- 3. Stacking of 5-10 shots
- 4. Automatic picking of first arrival times
- 5. Picking refinement with crosscorrelation

Tomographic imaging:

- 6. Anisotropy correction
- Iterative travel time inversion for V_Pimaging (after Lanz et al. 1998)

Lanz, E., H. Maurer and A. G. Green (1998). "Refraction tomography over a buried waste disposal site." Geophysics 63(4): 1414-1433.





Grab et al. (https://doi.org/10.5194/egusphere-egu2020-21588)

Receiver in borehole D3, sources in borehole D4





Results: P-wave velocity tomogram (baseline measurements)

Anisotropy of P-wave velocities V_P (Figure a):

- Average V_P parallel to bedding: 2870 m/s
- Average V_P normal to bedding: 2280 m/s
- Anisotropy slightly stronger in the foot wall compared to hanging wall
- Velocity corrected for anisotropy prior to travel-time inversion (Fig b),
- Clay bedding normal to tomographic plane (no off-plane effects due to anisotropy)





Figure a: Anisotropic P-wave velocities within tomographic plane (shown in Figure c).

Figure b: P-wave velocities corrected for their anisotropy.

Figure c: Tomographic plane with geophone locations (red triangles) and source locations (black dots).



Results: P-wave velocity tomogram (baseline measurements)

Figure a:

Tomogram with P-wave velocities (anisotropynormalized) with Main-Fault boundaries interpolated from borehole observations.

Figure b:

P-wave tomogram projected to its locations below niche 8 in the Mont Terri rock laboratory





Results: V_P-monitoring during step-up injection test

Injection location (a)

- Injection of CO₂saturated formation water in interval Q4 (figure a)
- Interval Q4 is 2 m off-plane relative to seismic tomographic plan
- Geophone locations
 (▼), and source
 location (◆ T23)

Injection protocol (b)

 Increase of injection pressure in 0.3 MPa steps every 10 min (figure b)



More information about this injection test:

Wenning et al. (EGU2020-19243), slide about "Testing for Fault Opening Pressure"



Results: V_P-monitoring during step-up injection test

Active Seismic monitoring

- P-wave sparker shots repeated after each injection step-up
- Change in P-wave velocity (dV_P), relative to V_P from baseline tomogram
- Figure a: dV_P at injection pressure of 2.4 MPa (first step)
- Figure b: dV_P at injection pressure of 4.5 MPa (last step)
- Reduction of V_P by around 1% in the vicinity of the injection interval





Discussion and Conclusion:

Baseline measurements for site characterization:

- Geology (Main Fault) resolved with P-wave travel-time tomography
- Anisotropy not uniform in hanging/foot wall (critical for V_P-tomography but less critical for dV_P tomography)

Time-lapse seismic during injection

- Travel time tomography sensitive to pressure induced effects (step-up test)
- During injection test, pressure in injection interval was increased from 2.4 MPa to 4.5 MPa. This resulted in a decrease of V_P by around 1%, which we were able to monitor and locate with active seismic monitoring.
- We interpret this as a poro-elastic effect, induced by pressure disturbance. This affects a volume which is much larger, than the volume within which the injected fluids were propagating (only very small fluid volume injected).





Acknowledgments:

We thank Christoph Bärlocher, David Jaeggi, Edgar Manukyan, Hansruedi Maurer, Jocelyn Gisiger, Leo Schwab, Linus Villiger, Maria Kakurina, Marija Lukovic, Nils Knornschild, Nima Gholizadeh, Paul Bossart, Semih Demir, Senecio Schefer, Thierry Theurillat, and Thomas Mörgeli for technical support, scientific advice, and/or on-site assistance.

Further thanks go to all the partners and collaborators of the CS-D experiment:



ACT ELEGANCY, Project No 271498, has received funding from DETEC (CH), BMWi (DE), RVO (NL), Gassnova (NO), BEIS (UK), Gassco, Equinor and Total, and is cofunded by the European Commission under the Horizon 2020 programme, ACT Grant Agreement No 691712.



This project is supported by the pilot and demonstration programme of the Swiss Federal Office of Energy (SFOE). It is conducted within the the Swiss Competence Center for Energy Research – Supply of Electricity (SCCER-SoE / Innosuisse)



SWISS COMPETENCE CENTER for ENERGY RESEARCH SUPPLY of ELECTRICITY Supported by:

Schweizerische Eidgenossenschaft Confédération suisse Confederazione Svizzera Confederaziun svizra Swiss Confederation

Innosuisse – Swiss Innovation Agency