



Estimating the hydrodynamic and morphodynamic characteristics using Entropy theory at the confluence of Negro and Solimões Rivers

Farhad Bahmanpouri¹, Silvia Barbetta¹, Carlo Gualtieri², Marco Ianniruberto³, Naziano Filizola⁴, Donatella Termini⁵, and Tommaso Moramarco¹

¹Italian National Research Council, Research Institute for Geo-Hydrological Protection (IRPI-CNR Perugia), Perugia, Italy

²Civil, Architectural and Environmental Engineering Department (DICEA), University of Napoli Federico II, Napoli 80125, Italy

³Universidade de Brasilia, Brasilia, DF, Brazil

⁴Universidade Federal do Amazonas, Manaus, AM, Brazil

⁵Dipartimento di Ingegneria, University of Palermo, Viale delle Scienze, 90128 Palermo, Italy

When two mega rivers merge the mixing of two flows results in a highly complex three-dimensional flow structure in an area known as the confluence hydrodynamic zone. In the confluence zone, substantial changes occur to the hydrodynamic and morphodynamic features which are of significant interest for researchers. The confluence of the Negro and Solimões Rivers, as one of the largest river junctions on Earth, is the study area of the present research. During the EU-funded Project “Clim-Amazon” (2011-2015), velocity data were collected using an ADCP vessel operating under high and low flow conditions in different locations at that confluence (Gualtieri et al., 2019). By applying the Entropy theory developed by Chiu (1988) for natural channels and simplified by Moramarco et al. (2014), the two-dimensional velocity distribution, as well as depth-averaged velocity, were calculated at the different transects along the confluence zone, using only the surface velocities observation. The estimated data yielded 6.6% and 6.9% error percentage for the discharge data related to high and low flow conditions, respectively, and 8.4% and 8.3% error percentage for the velocity data related to high and low flow conditions, respectively. Regardless of the flow condition, these preliminary results also suggest the potential points at the confluence zone for the maximum local scouring. The findings of the current research highlighted the potential of Entropy theory to estimate the flow characteristics at the large river's confluence, just starting from the measure of surface velocities. This is of considerable interest for monitoring high flows using no-contact technology, when ADCP or other contact equipment cannot be used for the safety of operators and risks for equipment loss.

Keywords: Amazon River, Negro/Solimões Confluence, Entropy Theory, Velocity Distribution, Local Scouring

References

Gualtieri, C., Ianniruberto, M., Filizola, N. (2019). On the mixing of rivers with a difference in density: the case of the Negro/Solimões confluence, Brazil. *Journal of Hydrology*, 578(11), November 2019, 124029,

Chiu, C. L. (1988). "Entropy and 2-D velocity distribution in open channels". *Journal of Hydrologic Engineering*, ASCE, 114(7), 738-756

Moramarco, T., Saltalippi, C., Singh, V.P. (2004). "Estimation of mean velocity in natural channels based on Chiu's velocity distribution equation". *Journal of Hydrologic Engineering*, ASCE, 9 (1), pp. 42-50