

EGU21-12188

<https://doi.org/10.5194/egusphere-egu21-12188>

EGU General Assembly 2021

© Author(s) 2022. This work is distributed under the Creative Commons Attribution 4.0 License.



Scaling seismic fault thickness from the laboratory to the field

Thomas P. Ferrand¹, Stefan Nielsen², Loïc Labrousse³, and Alexandre Schubnel⁴

¹Institut des Sciences de la Terre d'Orléans, Université d'Orléans / CNRS UMR-7327, Orléans, France.

²Department of Earth Sciences, Durham University, Durham DH1 5ED, United Kingdom.

³Institut des Sciences de la Terre de Paris, Sorbonne Université, Campus Pierre et Marie Curie / CNRS UMR-7193, Paris, France.

⁴Laboratoire de Géologie de l'Ecole Normale Supérieure, PSL Research University / CNRS UMR-8538, Paris France.

Pseudotachylytes originate from the solidification of frictional melt, which transiently forms and lubricates the fault plane during an earthquake. Here we observe how the pseudotachylyte thickness a scales with the relative displacement D both at the laboratory and field scales, for measured slip varying from microns to meters, over six orders of magnitude. Considering all the data jointly, a bend appears in the scaling relationship when slip and thickness reach ≈ 1 mm and $100 \mu\text{m}$, respectively, i.e. $M_w > 1$. This bend can be attributed to the melt thickness reaching a steady-state value due to melting dynamics under shear heating, as is suggested by the solution of a Stefan problem with a migrating boundary. Each increment of fault is heating up due to fast shearing near the rupture tip and starting cooling by thermal diffusion upon rupture. The building and sustainability of a connected melt layer depends on this energy balance. For plurimillimetric thicknesses ($a > 1$ mm), melt thickness growth reflects in first approximation the rate of shear heating which appears to decay in $D^{-1/2}$ to D^{-1} , likely due to melt lubrication controlled by melt + solid suspension viscosity and mobility. The pseudotachylyte thickness scales with moment M_0 and magnitude M_w ; therefore, thickness alone may be used to estimate magnitude on fossil faults in the field in the absence of displacement markers within a reasonable error margin.