

EGU21-8982

<https://doi.org/10.5194/egusphere-egu21-8982>

EGU General Assembly 2021

© Author(s) 2022. This work is distributed under the Creative Commons Attribution 4.0 License.



## Coupled HM modeling assists in designing CO<sub>2</sub> long-term periodic injection experiment (CO<sub>2</sub>LPIE) in Mont Terri rock laboratory

Dario Sciandra<sup>1,2,3</sup>, Víctor Vilarrasa<sup>1,2,3</sup>, Iman Rahimzadeh Kivi<sup>1,2</sup>, Roman Makhnenko<sup>4</sup>, Christophe Nussbaum<sup>5</sup>, and Dorothee Rebscher<sup>6</sup>

<sup>1</sup>Institute of Environmental Assessment and Water Research (IDAEA), Spanish National Research Council (CSIC), Barcelona, Spain

<sup>2</sup>Mediterranean Institute for Advanced Studies (IMEDEA), Spanish National Research Council (CSIC), Esporles, Spain

<sup>3</sup>Associated Unit: Hydrogeology Group UPC-CSIC, Barcelona, Spain

<sup>4</sup>Department of Civil and Environmental Engineering (CEE), Illinois University at Urbana-Champaign, Urbana, Illinois, USA

<sup>5</sup>Federal Office of Topography swisstopo, Wabern, Switzerland

<sup>6</sup>Bundesanstalt für Geowissenschaften und Rohstoffe (BGR), Hannover, Germany

We are performing a series of coupled hydro-mechanical (HM) simulations to model CO<sub>2</sub> flow through Opalinus Clay at the Mont Terri rock laboratory in the CO<sub>2</sub> Long-term Periodic Injection Experiment (CO<sub>2</sub>LPIE). CO<sub>2</sub>LPIE aims at inter-disciplinary investigations of the caprock sealing capacity in geologic CO<sub>2</sub> storage in a highly monitored environment at the underground laboratory scale. Numerical modeling allows us to gain knowledge on the dynamic processes resulting from CO<sub>2</sub> periodic injection and to assist the experimental design. The cyclic injection parameters (i.e., the period and the amplitude) have to be optimized for the field experiment and therefore different values are taken into account. Opalinus Clay is a claystone with nanoDarcy permeability that contains well developed bedding planes responsible for its anisotropic HM behavior. The hydraulic anisotropy is defined by a permeability parallel to the bedding planes being three times the one perpendicular to it. Additionally, the drained Young's modulus is measured to be 1.7 GPa parallel and 2.1 GPa perpendicular to bedding. Excavation reports by swisstopo document a SSE-dip of 45° for the bedding planes at the experiment location. CO<sub>2</sub> injection generates a mean overpressure of 1 MPa into the brine that propagates into the formation. The differential pressure between CO<sub>2</sub> and formation water, i.e., capillary pressure, is lower than the entry pressure and thus, CO<sub>2</sub> diffuses through the pores but does not advect in free phase. The liquid overpressure distribution is distorted by the hydraulic anisotropy, preferentially advancing along the bedding planes, as the associated permeability is higher than the one perpendicular to the bedding. The pore pressure buildup induces a poromechanical stress increase and an expansion of the rock that leads to a permeability enhancement of up to two orders of magnitude. The cyclic stimulation propagates through the domain faster and with a lag time and an attenuation, both of which increase with distance from the source with, their values being dependent on permeability, porosity and stiffness of the rock. As a result of the model orthotropy, the attenuation and the lag time change with direction, i.e. they are higher in the direction perpendicular to the bedding and lower in the direction parallel to the bedding. Given the very low permeability of Opalinus Clay, the

overpressure generated requires a long time to diffuse into the rock. Furthermore, the amplitude attenuation dissipates quite rapidly, so monitoring wells should be placed as close to the injection well as possible. The study of amplitude attenuation and time lag is necessary to determine how they can be utilized to evaluate the evolution of the HM properties as the rock is altered by the acidic nature of CO<sub>2</sub>-brine mixture. Comparison between field data and numerical simulations will be a useful asset to fill the gap.