

EGU23-17318, updated on 23 Apr 2024
<https://doi.org/10.5194/egusphere-egu23-17318>
EGU General Assembly 2023
© Author(s) 2024. This work is distributed under the Creative Commons Attribution 4.0 License.



Discrimination of sea ice leads and floes using Deep Learning applied to Sentinel-3 Ocean and Land Colour Instrument (OLCI) imaging spectrometer

Weibin Chen¹, Michel Tsamados¹, Rosie Willatt¹, So Takao², Connor Nelson¹, Isobel Lawrence³, Sanggyun Lee⁴, David Brockley⁵, Jack Landy⁶, Claude De Rijke-Thomas⁷, Dorsa Shirazi¹, Julienne Stroeve¹, and Alistair Francis⁸

¹Centre for Polar Observation and Modelling, Earth Sciences, University College London, London, UK

²Artificial Intelligence Institute, UCL

³ESRIN, European Space Agency, Italy/Centre for Polar Observation and Modelling, University of Leeds, UK

⁴Environmental Research Group, Research Institute of Industrial Science and Technology (RIST), South Korea

⁵Mullard Space Science Laboratory, University College London, London, UK

⁶University of Tromsø

⁷School of Geographical Sciences, University of Bristol, Bristol, UK

⁸PhiLab, ESRIN, European Space Agency, Italy

The Sentinel-3A and Sentinel-3B satellites, launched in February 2016 and April 2018 respectively, build on the legacy of CryoSat-2 by providing high-resolution radar altimetry data over the polar regions up to 81 degrees North. The combination of synthetic aperture radar (SAR) mode altimetry from Sentinel-3A and Sentinel-3B, and the Ocean and Land Colour Instrument (OLCI) imaging spectrometer, results in the creation of the first satellite platform that offers coincident optical imagery and SAR radar altimetry. We utilise these datasets to validate existing surface classification algorithms, in addition to investigating novel applications of deep learning to classify sea-ice from leads. This is important for estimating sea-ice thickness and to predict future changes in the Arctic and Antarctic regions. In particular, we propose the use of Vision Transformers (ViT) for this task and demonstrate their effectiveness, with accuracy reaching above 92%. We compare our automated results with human classification using the software IRIS.