



## Field and numerical study of wind-wave interaction at short fetches

Georgy Baydakov, Alexaandra Kuznetsova, Daniil Sergeev, Vladislav Papko, Alexander Kandaurov, Maxim Vdovin, and Yuliya Troitskaya

Institute of Applied Physics, 230, Nizhny Novgorod, Russian Federation (baidakov@km.ru)

Field measurements were carried out in 2012-2015 from May to October in the waters of Gorky Reservoir belonging to the Volga Cascade. The methods of the experiment focus on the study of airflow in the close proximity to the water surface. The sensors were positioned at the oceanographic Froude buoy including five two-component ultrasonic sensors WindSonic by Gill Instruments at different levels (0.1, 0.85, 1.3, 2.27, 5.26 meters above the mean water surface level), water and air temperature sensors, and system of the three wire wave gauge. One of wind sensors (0.1 m) was located on the float tracking the waveform for measuring the wind speed in the close proximity to the water surface.

Basic parameters of the atmospheric boundary layer (the friction velocity  $u_*$ , the wind speed  $U_{10}$  and the drag coefficient  $C_D$ ) were calculated from the measured profiles of wind speed. Parameters were obtained in the range of wind speeds of 1-12 m/s. For wind speeds stronger than 4 m/s  $C_D$  values were lower than those obtained before (see eg. [1,2]) and those predicted by the bulk parameterization. However, for weak winds (less than 3 m/s)  $C_D$  values considerably higher than expected ones. The new parameterization of surface drag coefficient was proposed on the basis of the obtained data.

The suggested parameterization of drag coefficient  $C_D(U_{10})$  was implemented within wind input source terms in WAVEWATCH III [3]. The results of the numerical experiments were compared with the results obtained in the field experiments on the Gorky Reservoir. The use of the new drag coefficient improves the agreement in significant wave heights  $H_S$  [4]. At the same time, the predicted mean wave periods are overestimated using both built-in source terms and adjusted source terms. It is shown, that variation in the nonlinear scheme DIA has a significant effect on the result of the simulation

The work was supported by the Russian Foundation for Basic Research (Grants No. 15-35-20953, 14-05-00367, 15-45-02580, 16-35-80022) and project ASIST of FP7. The field experiment is supported by Russian Science Foundation (Agreement No. 15-17-20009), numerical simulations are partially supported by Russian Science Foundation (Agreement No. 14-17-00667).

### References

1. A.V. Babanin, V.K. Makin Effects of wind trend and gustiness on the sea drag: Lake George study // Journal of Geophysical Research, 2008, 113, C02015, doi:10.1029/2007JC004233
2. S.S. Atakturk, K.B. Katsaros Wind Stress and Surface Waves Observed on Lake Washington // Journal of Physical Oceanography, 1999, 29, pp. 633-650
3. Kuznetsova A.M., Baydakov G.A., Papko V.V., Kandaurov A.A., Vdovin M.I., Sergeev D.A., Troitskaya Yu.I. Adjusting of wind input source term in WAVEWATCH III model for the middle-sized water body on the basis of the field experiment // Hindawi Publishing Corporation, Advances in Meteorology, 2016, Vol. 1, article ID 574602
4. G.A. Baydakov, A.M. Kuznetsova, D.A. Sergeev, V.V. Papko, A.A. Kandaurov, M.I. Vdovin, and Yu.I. Troitskaya Field study and numerical modeling of wind and surface waves at the middle-sized water body // Geophysical Research Abstracts, Vol.17, EGU2015-9427, Vienne, Austria, 2015.